



Keyless Drill Chucks

**SPECIAL
HEAVY DUTY TYPE**

TYPE: XHSP



- Special design & manufacture against for super heavy torque (Clamping capacity) use.
- Owing to inspecting strictly & with excellent RUNOUT Accuracy and quality guanteed the gripping power is double than the general brand.
- Avoid the drill dropped when used in instaneous change of direction and equipped with spanner hole for tightening perfect safety.
- Especially suitable for CNC machining center & milling machine use.
- Accuracy: 50mm length within 0.05mm
- The key is optional

Unit:mm

ORDER NO.	Type	Clamping Capacity mm inch	Female Taper DIN or jacobcs	OUTER Ø mm	Length		Wt g	QTY Pcs./ Cu-Ft	N.W/G.W kge	CODE NO.
					open B mm	closed A mm				
11014	8XHSP	0-8 0-5 / 16"	J2	36	61	69	320	40/0.6	13/14	3302-001
11015			B10	36	61	69	320	40/0.6	13/14	3302-002
11016			J1	36	61	69	320	40/0.6	13/14	3302-003
11017			B12	36	61	69	320	40/0.6	13/14	3302-004
11018	10XHSP	0-10 0-3 / 8"	J33	43	81	92	700	40/0.6	28/29	3302-005
11019			J2S	43	81	92	700	40/0.6	28/29	3302-006
11020			B12	43	81	92	700	40/0.6	28/29	3302-007
11021			B16	43	81	92	700	40/0.6	28/29	3302-008
11025	13XHSP	0-13 0-1 / 2"	J6	51.5	92	103	1030	30/0.6	31/32	3302-009
11026			J33	51.5	92	103	1035	30/0.6	31/32	3302-010
11027			B16	51.5	92	103	1030	30/0.6	31/32	3302-011
11028			J6	58	95	108	1450	24/0.6	35/36	3302-012
11029	16XHSP	3-16 1-8 - 5/8"	B16	58	95	108	1450	24/0.6	35/36	3302-013
11030			B18	58	95	108	1450	24/0.6	35/36	3302-014
11035			J3	58	95	108	1450	24/0.6	35/36	3302-015
11031	Key	13XHSP								3304-001
11032		16XHSP								3304-002
11033		8XHSP								3304-003
11034		10XHSP								3304-004
17000	6XHSP	0.5-6.5 1/64"-1/4"	B12	34	61	69	320	8/0.6	26/27	3304-010
17002			J1	34	61	69	320	8/0.6	26/27	3304-011
17004			B10	34	61	69	320	8/0.6	26/27	3304-012



Keyless Drill Chucks

STANDARD TYPE

TYPE: H



- Industrial design especially for life and safety while in operation.
- All hardened parts ensure long milling machines and drilling machines.
- Accuracy: 35 m/m length within 0.08 m/m

Unit:mm

ORDER NO.	Type	Clamping Capacity mm inch	Female Taper DIN or jacobcs	OUTER Ø mm	Length		Wt g	CODE NO.
					open B mm	closed A mm		
11061	6H	0-6.5	J1	34	61	69	320	3302-030
11062		0-1 / 4"	B10	34	61	69	320	3302-031
11063	8H	0-8	J1	34	61	69	340	3302-032
11064		0-5 / 16"	B10	34	71	69	340	3302-033
11065	10H	0-10 0-3 / 8"	J2S	42.5	81	92	700	3302-034
11066			J33	42.5	81	92	700	3302-035
11067			B12	42.5	81	92	705	3302-036
11068			B16	42.5	81	92	705	3302-037
								3302-038
11070	13H	0-13 0-1 / 2"	J6	50.5	92	103	1030	3302-039
11071			J33	50.5	92	103	1035	3302-040
11072			B16	50.5	92	103	1030	3302-041
11073	16H	3-16 1-8 - 5/8"	J6	50.5	92	103	1030	3302-042
11074			B16	50.5	92	103	1030	3302-043
11075			B18	50.5	97	108	1040	3302-044